

Principle Specifications

		SH330-5	SH330LC-5	SH350HD-5	SH350LHD-5
		STD Specifications			
Base	Boom length	6.45 m		6.45 m (HD type)	
	Arm length	3.25 m		3.25 m (HD type)	
	Bucket capacity (ISO heaped)	1.40 m ³		1.40 m ³ (HD type)	
	Std.operating weight	33 400 kg	34 000 kg	35 600 kg	36 100 kg
Engine	Make & model	ISUZU AH-6HK1XYSS			
	Rated output	202 kw/2 000 min ⁻¹			
	Piston displacement	7 790 ml(cc)			
Hydraulic System	Main pump	2 variable displacement axial piston pumps			
	Max. pressure	34.3 Mpa			
	(with auto power boost)	37.3 Mpa			
	Travel motor	Variable displacement axial piston motor			
	Parking brake type	Mechanical disc brake			
	Swing motor	Fixed displacement axial piston motor			
Performance	Travel speed	5.5/3.5 km/h			
	Traction force	265 kN	265 kN	264 kN	264 kN
	Grade ability	70%<35°>			
	Ground pressure	67 kPa	64 kPa	72 kPa	67 kPa
	Swing speed	9.8 min ⁻¹			
	Bucket	229 kN			
	/with power boost	248 kN			
	Arm	164 kN			
	/with power boost	178 kN			
Others	Fuel tank	580 lít			

	Hydraulic fluid tank	350
--	----------------------	-----